



I SQUARED R ELEMENT CO., INC.

12600 Clarence Center Road, P.O. Box 390, Akron, New York 14001, Phone (716)542-5511, Fax (716)542-2100
e-mail: sales@isquaredrelement.com www.isquaredrelement.com

INFORMATION NORMALLY REQUIRED TO MAKE MOLYBDENUM DISILICIDE ELEMENT RECOMMENDATIONS

DESCRIBE FURNACE OR KILN: _____

DESCRIBE PROCESS: _____

NORMAL OPERATING TEMP. _____ MAXIMUM DESIGN TEMP. _____

ATMOSPHERE: _____

OPERATION: CONTINUOUS - OR - BATCH _____

FIRING CYCLE: HEAT UP TIME to TEMP: _____ SOAK TIME @ TEMPERATURE: _____

PLEASE PROVIDE DIMENSIONED SKETCH FOR LOAD, HOT CHAMBER AND DOOR LOCATION

LOAD DIMENSION: (LENGTH x WIDTH x HEIGHT): _____

HOT CHAMBER DIMENSION (LENGTH x WIDTH x HEIGHT): _____

WALL THICKNESS and COMPOSITION: _____

TEMPERATURE UNIFORMITY REQUIRED: _____

WILL ATMOSPHERE BE CONTAINED IN MUFFLE? _____

MUFFLE COMPOSITION: _____

IF CONTINUOUS, HOW IS MATERIAL TRANSPORTED THROUGH KILN? _____

WEIGHT OF MATERIAL TO BE HEATED PER HOUR _____

WILL ANY VOLATILES BE GIVEN OFF DURING FIRING? _____

ESTIMATED POWER REQUIRED KW/HR: _____

INCOMING VOLTAGE: _____ MAXIMUM AMPS AVAILABLE: _____

SINGLE PHASE OR THREE PHASE: _____

METHOD OF POWER CONTROL, Zero Cross SCR, phase angle?

HOW MANY ZONES OF TEMPERATURE CONTROL? _____

IS MULTIPLE TAP TRANSFORMER AVAILABLE? _____

RATED KW: _____ 1 OR 3 PHASE _____

MAXIMUM SECONDARY AMPERES & VOLTAGE TAPS: _____

CONTACT NAME: _____

COMPANY: _____

ADDRESS: _____

TELEPHONE: (_____) _____ FAX (_____) _____